



		A
M	EG	Д

FABRIC TYPE COMPOSITION DURABILITY LIGHTFASTNESS FEATURES FIRE TESTS

PU Leather 100% Polyurethane 500,000 Martindale 5 High Scratch Resistance Chemical Solvents Free EN 1021-1 - Cigarette Test PASS

CA Tech. Bull. 117:2013 / NFPA 260 - Cigarette Test PASS



FLORIDA

LEATHER TYPE

Corrected Leather

AVERAGE SKIN THICKNESS

0.8 - 1.0 mm

Brazilian Bovine

RAWHIDE

PREPARATION

Corrected and Embossed Grain

Protective Top Coat, Soft Handle and Silky Matte Finish

FIRE TESTS

BS 5852:1979 BS EN 1021-1-2:2006



ATLANTIDA

Aniline Leather

AVERAGE SKIN THICKNESS

1.2 - 1.4 mm European Bovine

RAWHIDE

PREPARATION

Lightly Buffed Natural Grain

FIRE TESTS

BS 5852:1979

BS EN 1021-1-2:2006



COLUMBIA

LEATHER TYPE Nubuck Leather

AVERAGE SKIN THICKNESS

1.2 - 1.4 mm

RAWHIDE

European Bovine

PREPARATION

Natural Grain Aniline Dyed, Suede Look, Liquid Repellent FIRE TESTS

BS 5852:1979

BS EN 1021-1-2:2006

